

HCO-HuntingCamOnline
Infrared Digital Scouting Camera

ScoutGuard Series SG550 SG530 Specifications

Tel: 1-803-223-9710 Fax: 1-803-334-4505
 Email: sales@huntingcamonline.com Web: www.huntingcamonline.com

Image Sensor	5MP(SG550) Color CMOS sensor 3MP(SG530) Color CMOS sensor
Maximum Resolution	2560x1920(SG550) 2048x1536(SG530)
Lens	F=3.1mm FOV(Field of View)=40° Auto IR-Cut-Remove (Night)
IR-Flash	40Ft
Remote Control Display	1.7" LCD
Internal Memory	N/A
External Memory	SD-card from 8MB to 2GB
Picture Resolution	5MP = 2560x1920 3MP = 2048x1536
Video Resolution	640x480(Default, 16FPS) 320x240(20FPS)
PIR Lens	Multi Zone
PIR sensitivity	Adjustable(High/Normal/Low)
IR Bulbs	22 Long Range IR Emitters
Operation	Day/Night(24hours)
Trigger Time	1.2s
Delay	1s – 60m Programmable
Capture Mode	1~3 Programmable
Video Length	1-60s Programmable
Power Supply	8xAA(Recommended) 4xAA(Emergency) 6V DC
Stand-by Current	< 0.3mA(<7mAh/Day)
Power Consumption	150mA (+450mA When IR-LED Lighted)
Low Battery Alert	LED Indicator
User Interface	Remote Control With LCD Display
Ports & Jacks	Remote Control Jack TV Out Jack USB Jack SD Card Slot 6V DC Jack
Mounting	Strap Cable Lock Up To Φ 3/8 Inches Nail/Screw Lock Up To up to Φ 3/16 Inches
Dimensions	Heights: 5-1/2 inches Width: 3-1/4 inches Depth: 2 inches
Weight	Approximate 1 lb With Battery
Operation Temperature	-4F to 140F
Storage Temperature	-22F to 158F
Operation Humidity	5% - 90%
Security authentication	FCC
Visit us at www.HuntingCamOnline.com for more information!	